



## E-UPS 12VDC Uninterruptible Power Supply

### Description

The E-UPS used in conjunction with Electroline ED2-B and ED3-B (R-ONU) micro nodes, is a 12Vdc uninterruptable Power System used to power network communications.

The unit is designed and sized for a minimum of 8 hours back up should the primary 110/220 VAC power system be disrupted.

An optional 24-hour model is also available. The E-UPS with its intelligent battery re-charging feature gives the user the satisfaction of knowing that this power supply will give years of life.

The E-UPS is designed for interior mounting, with a hot swappable battery pack. The E-UPS can be mounted remotely from the micro node to allow the installer the flexibility to mount the unit close to an existing power outlet.

### Applications

Used where critical 12 VDC power is required during local power outages for up to 8-hours or to 24-hours.



### Features:

- Sealed lead-acid battery
- Compact
- LED and audio alarms
- Auto re-charge
- 24 watt continuous power capability
- Intelligent re-charging
- Hot swap battery replacement
- 8-Hour battery Pack shipped with unit
- 24 hour model available
- RoHS compliant
- UL/ CSC certified
- 2-years warranty
- End-User friendly

# E-UPS

## 12VDC Uninterruptable Power Supply

### Technical Specifications:

Area of use	Interior
Voltage/ Frequency Range	87-264 VAC/ 40-70 Hz
On Battery Output Voltage	12 VDC
Sealed, Maintenance Free Lead Acid Battery	7.2AH/12V
Continuous Power	24Watt
Typical Battery Life	3-5 years
Typical Recharge time	Up to 18 hour
User replaceable	Hot Swappable
Audible Indicator	Utility Failure, Low Battery
LED Indicators:	AC input, Output Voltage, Battery
Operating Temperature	0-40 degree C (32-104 degree F )
Dimensions	9.25 x 6.25 x 3.50 inch
Weight	7.3 lbs
Carton Dimensions	14 x 14 x 4.7
Carton Weight	9.5 lbs

### ORDERING INFORMATION:

E-NID	-	UPS	-	1	1
Model Series		Product Type		Backup time option	Miscellaneous options
E-NID	-	UPS	-	1 =UPS with 8 hours backup time 2 =UPS with 24 hours backup time	1=Power inserter + cable adaptor 0= No miscellaneous option

### Options/ Replacement Parts:

E-NID	-	BATT	-	1
Model Series		Product Type		Battery
E-NID	-	BATT	-	1 = Battery for 8 hours backup time 2 = Battery for 8 hours backup time

**Corporate Headquarters**  
**Electroline Equipment Inc.**  
 395 Lebeau Blvd.,  
 Saint-Laurent, Québec H4N 1S2  
 Canada

**Telephone**  
 North America (800) 461-3344  
 Elsewhere (514) 374-6335

**Fax**  
 Corporate / Ordering:  
 (514) 374-2257

**General Inquiries**  
[info@electroline.com](mailto:info@electroline.com)  
**Technical Support**  
[support@electroline.com](mailto:support@electroline.com)